



October 2010

Space Roll

For walls, floors and roofs

Description

Space Roll is a flexible, lightweight, low density, non-combustible glass mineral wool roll with high tear strength.

Application

Space Roll is intended for use as a general purpose thermal and acoustic product for a wide range of applications.

Standards

Space Roll is non-combustible inorganic glass wool, defined as mineral wool in EN ISO 9229 and is manufactured in accordance with Quality Assurance Standard EN ISO 9001, and product standard EN 13162.

Durability

Space Roll is rot proof, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria, it is odourless and non - hygroscopic.

Vapour resistance - resistivity

Space Roll offers negligible resistance to the passage of water vapour and has a vapour resistivity of 7.00 MN.s.g.m.

Performance

Thermal

Space Roll has a thermal conductivity of 0.039 W/mK.

Fire

Space Roll is classified as Euroclass A1 to EN ISO 13501-1.

Acoustics

Space Roll has excellent sound absorption performance.

Benefits

- Euroclass A1 to EN ISO 13501-1
- Lightweight and economic insulation quilt
- Exceptionally high tear strength
- Provides thermal and acoustic performance
- Quick and easy to use and install
- Lightweight and easy to handle

Space Roll

Environmental

Space Roll is free from CFCs, HCFCs and any other material with ozone depletion potential in its manufacture and content and represents no known threat to the environment. **It's manufacture has a low impact on the environment and is classified as Zero ODP and Zero GWP.**

Handling and storage

Space Roll is easy to handle and install, being lightweight and easily cut to size, where necessary. Space Roll is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored inside, or under cover and off the ground. Space Roll should not be left permanently exposed to the elements.

Thickness	Thermal conductivity	Thermal resistance	Width	Length	Area per pack
(mm)	(W/mK)	(m ² K/W)	(mm)	(mm)	(m ²)
50	0.039	1.25	2x570	22000	25.08
70	0.039	1.75	2x570	16000	18.24
100	0.039	2.55	2x570	11000	12.54
125	0.039	3.21	2x570	8950	10.20
150	0.039	3.80	2x570	7200	8.21

Note: Other thicknesses are available but subject to availability and request.

Knauf Insulation mineral wool products with ECOSE® Technology benefit from a natural, formaldehyde-free binder made from rapidly renewable organic materials instead of petroleum-based chemicals and is up to 70% less energy intensive. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE® Technology contain no dye or artificial colours – the colour is completely natural.

Knauf Insulation Ltd

PO Box 10
Stafford Road
St Helens
Merseyside
WA10 3NS
UK

Tel: 0800 14 66 22

Fax: +44 (0)1744 766732

Email: info@knaufinsulation.fi

For the contact details of your nearest Knauf Insulation Business Development Manager, please call the above number.