



October 2010

## Space Slab

### For walls, floors and roofs

#### Description

Space Slab is a flexible, lightweight, non-combustible, glass mineral wool slab with a high tear strength.

#### Application

Space Slab is a general purpose slab for thermal and acoustic insulation, and is suitable for use in a wide range of applications.

#### Standards

Space Slab is non-combustible inorganic glass wool, defined as mineral wool in EN ISO 9229 and is manufactured in accordance with Quality Assurance Standard EN ISO 9001, and product standard EN 13162.

#### Durability

Space Slab is rot proof, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria, it is odourless and non-hygroscopic.

#### Vapour resistance - resistivity

Space Slab offers negligible resistance to the passage of water vapour and has a vapour resistivity of 7.00 MN.s.g.m.

### Performance

#### Thermal

Space Slab has a thermal conductivity of 0.035 or 0.039 W/mK.

#### Fire

Space Slab is classified as Euroclass A1 to EN ISO 13501-1.

#### Acoustics

Space Slab has excellent sound absorption performance.

### Benefits

- Provides thermal, acoustic and fire performance
- Lightweight and easy to handle and cut
- Versatile multi-purpose product
- Exceptionally high tear strength
- Quick and easy to use and install

## Space Slab

### Environmental

Space Slab is free from CFCs, HCFCs and any other material with ozone depletion potential in its manufacture and content and represents no known threat to the environment. **Space Slab's manufacture has a low impact on the environment and is classified as Zero ODP and Zero GWP.**

### Handling and Storage

Space Slab is easy to handle and install, being lightweight and easily cut to size, where necessary. It is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Space Slab should not be left permanently exposed to the elements.

Thickness	Thermal conductivity	Thermal resistance	Width	Length	Area per pack
(mm)	(W/mK)	(m <sup>2</sup> K/W)	(mm)	(mm)	(m <sup>2</sup> )
50	0.039	1.25	565	1170	10.58
70	0.039	1.75	565	1170	7.93
100	0.039	2.55	565	1170	7.93
125	0.039	3.20	565	1170	7.93
150	0.039	3.80	565	1170	5.29
50	0.035	1.40	570	1170	10.67
70	0.035	2.00	570	1170	8.00
100	0.035	2.85	570	1170	5.34
125	0.035	3.55	570	1170	4.00
150	0.035	4.25	570	1170	3.33
175	0.035	5.00	570	1170	2.67

Note: Other thicknesses are available but subject to availability and request.



Knauf Insulation mineral wool products with ECOSE® Technology benefit from a natural, formaldehyde-free binder made from rapidly renewable organic materials instead of petroleum-based chemicals and is up to 70% less energy intensive. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE® Technology contain no dye or artificial colours – the colour is completely natural.

### Knauf Insulation Ltd

PO Box 10  
Stafford Road  
St Helens  
Merseyside  
WA10 3NS  
UK

**Tel:** 0800 14 66 22

**Fax:** +44 (0)1744 766732

**Email:** [info@knaufinsulation.fi](mailto:info@knaufinsulation.fi)

For the contact details of your nearest Knauf Insulation Business Development Manager, please call the above number.